

DG1016



16CH HD CCTV DVR

FEATURES

Cloud Service - EaZy Networking*

- ❖ EaZy Networking, the cloud service provided by AVTECH, available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- ❖ The “Buddy” feature to share the device access permission to other people.
- ❖ Device login / out notifications reported.

Push Status -

Active Event Notification with EagleEyes App

- ❖ Push Status to send instant notifications for system events, such as video loss or HDD data removal.



HD Video Recording

- ❖ HD real-time recording brings users clear images while video recording and playback
- ❖ 1920*1080 Full HD video output service, giving the best image quality on LCD / LED monitors

Remote Surveillance

- ❖ Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
- ❖ Video Viewer for 16 devices central management
- ❖ Applicable also to Apple’s media player, QuickTime.

Independent Channel Control

- ❖ Definable “Resolution” / “Quality” / “IPS” by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

- ❖ Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

Backup Function

- ❖ Supports USB flash drive and network backup.

▶ SPECIFICATIONS

▼ Video	
Video System	NTSC / PAL (auto detection)
Video Compression Format	H.264
Video Input	16 channels (Composite video signal 1 Vp-p 75Ω BNC)
Video Output	BNC YES
	VGA YES
	HDMI YES
▼ Record & Backup	
Maximum Recording Rate	1080P 1920 x 1080 pixels with 240 IPS 720P 1280 x 720 pixels with 480 IPS QHD 960 x 540 pixels with 480 IPS Frame 704x480 pixels with 480 IPS <NTSC> / 704x576 pixels with 400 IPS <PAL> Field 704x240 pixels with 480 IPS <NTSC> / 704x288 pixels with 400 IPS <PAL> CIF 352x240 pixels with 480 IPS <NTSC> / 352x288 pixels with 400 IPS <PAL>
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Pre-alarm Recording	YES
Playback Channel	16CH
Quick Search	Time / Motion / Alarm search mode
Backup Device	USB 2.0 flash drive / Network
▼ Audio	
Audio Input	2 audio inputs
Audio Output	1 Audio output (Mono)
▼ General	
Hard Disk Storage**	Up to 3 SATA HDDs
SATA Interface	YES
Image Quality Setting	SUPER BEST / BEST / HIGH / NORMAL
USB Mouse Control	YES
Motion Detection Area	16 × 12 grids per channel
Motion Detection Sensitivity	3 adjustable parameters for accurate detection
Event Notification	Push Status / FTP / E-Mail
Picture Zoom	2X digital zoom
PTZ Control	YES
Alarm I/O	4 inputs, 1 output
RS485	YES
IR Remote Control	YES (IR receiver built-in)
Key Lock (Password Protection)	YES
User Level	4 user levels for different access privilege
Video Loss Detection	YES
Camera Title	Supports up to 12 letters
Video Adjustable	Hue / Saturation / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY & MM/DD/YY
Daylight Saving	YES
Power Source (±10%)	DC19V / 3.42A
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)
Dimensions (mm)***	432(W) × 90(H) × 326(D)
▼ Network	
Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS

▶ SPECIFICATIONS

▼ Remote Surveillance from PC		
Compatible Operating System	Windows & MAC	
Compatible Program	Web Browser:	Internet Explorer, Mozilla Firefox, Google Chrome & Safari
	Video Viewer:	16CH central management software for Windows and MAC operating systems
	QuickTime:	For both Windows and MAC operating systems
Max. online users	10	
Web Transmitting Compression Format	H.264	
Network Live Audio	YES	
Remote Independent Operation	YES	
Remote Event Download & Playback	YES	
▼ Mobile Surveillance		
App	EagleEyes	
Compatible Devices	iOS & Android devices	
Push Status	YES	
▼ Others		
EaZy Networking	YES	
DCCS Support	YES	
AVTECH Free DDNS service	YES	
Multiplex Operation	Live display / record / playback / backup / network operations	
System Recovery	System auto recovery after power failure	
Optional Peripherals	HDMI Matrix (HDM02)	

* The specifications are subject to change without notice.

** 1 HDD capacity up to 4TB

*** Dimensional tolerance: ±5mm

▶ REAR PANEL

